

Safety Data Sheet (SDS) Report

Applicant: BE CREATIVE ARTS AND CRAFTS CO.,LTD Issue Date: 2019-06-29

Sample Description:

The sample information was submitted and identified on client's behalf to be:

Product Name : Alcohol Based Ink

LIPSTICK RED (R62), SUNFLOWER (Y53), BLUE CRYSTAL(B92), MAY GREEN (G71),

MAUVE(V103), ORANGE RED (O21), PURPLE VOILET(V51), FULVOUS(O60),

NEUTRAL GERY4 (NG4), BLACK (XB)

Brand :

Physical State : Liquid

Data Received : June 13, 2019
Last Information Date : June 29, 2019
Data Reviewed : June 29, 2019

Service Requested:

Based on the information provided by the applicant, the Safety Data Sheet (SDS) was generated in accordance with requirements of OSHA HazCom Standard (2012), for details please refer to attached pages.

Authorized By:

On Behalf Of Regulatory Affairs in Intertek Testing Services Ltd., Shanghai

Anna Wang

Regulatory Consultant

This report shall not be reproduced except in full, without the written approval of the laboratory.

SDS number:

SHI109472012

Intertek Health, Environmental & Regulatory Services (HERS)

5th Floor,Building No.86,1198 QinZhou Road(North),Cao Hejing Development Zone,ShangHai,China.

Tel: +86 021 53397917 ZIP: 200233 E-mail:hers@intertek.com

Safety Data Sheet

Alcohol Based Ink

BE CREATIVE ARTS AND CRAFTS CO.,LTD

SDS number:**SHI109472012**

Issue Date:29/06/2019 GHS.USA.EN

Version No:**1.0**According to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Alcohol Based Ink	
Proper shipping name	ne FLAMMABLE LIQUID, N.O.S. (contains ethanol)	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses	Art, Coloring and Crafting

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Applicant name	BE CREATIVE ARTS AND CRAFTS CO.,LTD	
Address	2ND FLOOR,BUL 10,FUTIAN 4TH SECTION,NORTH OF GONGREN ROAD,YIWU,ZHEJIANG,CHINA.	
Telephone		
Email		
Manufacturer name	BE CREATIVE ARTS AND CRAFTS CO.,LTD.	
Address	2ND FLOOR,BUL 10,FUTIAN 4TH SECTION,NORTH OF GONGREN ROAD,YIWU,ZHEJIANG,CHINA.	
Telephone	+86-579-81572769	
Fax	+86-579-89159482	
Emergency telephone	+86-18868487309	
Email	cs1@becreativeartscrafts.com	
Importer name		
Address		
Telephone		
Email		

Emergency phone number

Emergency priorie number		
Association / Organisation		
Emergency telephone numbers		

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Classified as Dangerous Goods for transport purposes.

Classification

Flammable Liquid Category 2, Skin Sensitizer Category 1, Specific target organ toxicity - single exposure Category 3 (narcotic effects), Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3

Label elements

Hazard pictogram(s)





SIGNAL WORD DANGER

Hazard statement(s)

H225	Highly flammable liquid and vapour.	
H317	May cause an allergic skin reaction.	
H336	May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effects.	

Hazard(s) not otherwise classified

Supplementary statement(s)

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	

Precautionary statement(s) Prevention

P210	(eep away from heat/sparks/open flames/hot surfaces No smoking.	
P233	Keep container tightly closed.	
P271	Use in a well-ventilated area.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P240	Ground/bond container and receiving equipment.	
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P261	Avoid breathing mist/vapours/spray.	
P273	Avoid release to the environment.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P363	Wash contaminated clothing before reuse.	
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No %[weight] Name 64-17-5 63.87-70 ethanol 107-98-2 20 Proprylene glycol monomethyl ether 8050-09-7 10 rosin-colophony 12227-67-7 0-3.37 C.I. Solvent Yellow 82 82347-07-7 0-2.76 C.I. Solvent Red 218 61901-95-9 0-2.14 C.I. Solvent Yellow 62 37229-23-5 0-2.1 C.I. Solvent Blue 45 6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37 52256-37-8 0-0.24 C.I. Acid Orange 92				
107-98-2 20 Proprylene glycol monomethyl ether	CAS No	%[weight]	Name	
8050-09-7 10 rosin-colophony 12227-67-7 0-3.37 C.I. Solvent Yellow 82 82347-07-7 0-2.76 C.I. Solvent Red 218 61901-95-9 0-2.14 C.I. Solvent Pellow 62 37229-23-5 0-2.1 C.I. Solvent Blue 45 6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	64-17-5	63.87-70	ethanol	
12227-67-7 0-3.37 C.I. Solvent Yellow 82 82347-07-7 0-2.76 C.I. Solvent Red 218 61901-95-9 0-2.14 C.I. Solvent Yellow 62 37229-23-5 0-2.1 C.I. Solvent Blue 45 6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	107-98-2	20	Proprylene glycol monomethyl ether	
82347-07-7 0-2.76 C.I. Solvent Red 218 61901-95-9 0-2.14 C.I. Solvent Yellow 62 37229-23-5 0-2.1 C.I. Solvent Blue 45 6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	8050-09-7	10	rosin-colophony	
61901-95-9 0-2.14 C.I. Solvent Yellow 62 37229-23-5 0-2.1 C.I. Solvent Blue 45 6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	12227-67-7	0-3.37	C.I. Solvent Yellow 82	
37229-23-5 0-2.1 C.I. Solvent Blue 45 6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	82347-07-7	0-2.76	C.I. Solvent Red 218	
6320-14-5 0-1 C.I. Basic Red 12 12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	61901-95-9	0-2.14	C.I. Solvent Yellow 62	
12237-31-9 0-0.97 C.I. Solvent Yellow 79 94765-62-5 0-0.87 C.I. Solvent Black 45 61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	37229-23-5	0-2.1	C.I. Solvent Blue 45	
94765-62-5 0-0.87 <u>C.I. Solvent Black 45</u> 61901-92-6 0-0.7 <u>C.I. Solvent Red 91</u> 1325-86-6 0-0.52 <u>C.I. Solvent Blue 5</u> 12220-53-0 0-0.44 <u>C.I. Acid Violet 66</u> 12237-24-0 0-0.43 <u>C.I. Solvent Blue 70</u> 6358-36-7 0-0.42 <u>C.I. Basic Yellow 37</u>	6320-14-5	0-1	C.I. Basic Red 12	
61901-92-6 0-0.7 C.I. Solvent Red 91 1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	12237-31-9	0-0.97	C.I. Solvent Yellow 79	
1325-86-6 0-0.52 C.I. Solvent Blue 5 12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	94765-62-5	0-0.87	C.I. Solvent Black 45	
12220-53-0 0-0.44 C.I. Acid Violet 66 12237-24-0 0-0.43 C.I. Solvent Blue 70 6358-36-7 0-0.42 C.I. Basic Yellow 37	61901-92-6	0-0.7	C.I. Solvent Red 91	
12237-24-0 0-0.43 <u>C.I. Solvent Blue 70</u> 6358-36-7 0-0.42 <u>C.I. Basic Yellow 37</u>	1325-86-6	0-0.52	C.I. Solvent Blue 5	
6358-36-7 0-0.42 <u>C.I. Basic Yellow 37</u>	12220-53-0	0-0.44	C.I. Acid Violet 66	
	12237-24-0	0-0.43	C.I. Solvent Blue 70	
52256-37-8 0-0.24 <u>C.I. Acid Orange 92</u>	6358-36-7	0-0.42	C.I. Basic Yellow 37	
	52256-37-8	0-0.24	C.I. Acid Orange 92	

61901-87-9 0-0.2 <u>C.I. Solvent Black 29</u>

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may re	sult
--	------

Special protective equipment and precautions for fire-fighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive.
Fire/Explosion Hazard	Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. Remove all ignition sources. Clean up all spills immediately.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs.
Other information	 Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	Plastic case,Cardboard box
--------------------	----------------------------

Storage incompatibility

- ▶ Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.
- Avoid strong bases.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethanol	Alcohol, Cologne spirit, Ethanol, EtOH, Grain alcohol	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethanol	Ethanol	Not Available	1000 ppm	Not Available	TLV® Basis: URT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ethanol	Ethyl alcohol (Ethanol)	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Proprylene glycol monomethyl ether	Dowtherm® 209, 1-Methoxy-2-hydroxypropane, 1-Methoxy-2-propanol, 2-Methoxy-1-methylethanol, Propylene glycol methyl ether	100 ppm / 360 mg/m3	540 mg/m3 / 150 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	Proprylene glycol monomethyl ether	1-Methoxy-2-propanol	50 ppm	100 ppm	Not Available	TLV® Basis: Eye & URT irr
US ACGIH Threshold Limit Values (TLV)	rosin-colophony	Rosin core solder thermal decomposition products (colophony)	Not Available	Not Available	Not Available	TLV® Basis: Skin sens; dermatitis; asthma

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethanol	Ethyl alcohol; (Ethanol)	Not Available	Not Available	15000 ppm
Proprylene glycol monomethyl ether	Propylene glycol monomethyl ether; (Ucar Triol HG-170)	100 ppm	160 ppm	660 ppm
rosin-colophony	Rosin core solder decomposition products; (Colophony Gum)	72 mg/m3	790 mg/m3	1,500 mg/m3

Ingredient	Original IDLH	Revised IDLH
ethanol	3,300 ppm	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.▶ Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
Body protection	See Other protection below
Other protection	► Overalls. ► PVC Apron.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	LIPSTICK RED (R62),SUNFLOWER (Y53) ,BLUE CRYSTAL(B92) ,MAY GREEN (G71) ,MAUVE(V103) ,ORANGE RED (O21) ,PURPLE VOILET(V51) ,FULVOUS(O60),NEUTRAL GREY4 (NG4),BLACK (XB) Liquid Ink			
Physical state Liquid Relative density (Water = 1) Not Available				
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological e	effects
	ethanol
	Inhalation (rat) LC50: 124.7 mg/l/4H ^[2]
	Proprylene glycol monomethyl ether
	dermal (rat) LD50: >2000 mg/kg ^[1]
	Inhalation (rat) LC50: 12485.7375 mg/l/5h.d ^[2]
	Oral (rat) LD50: 3739 mg/kg ^[2]
	rosin-colophony
	dermal (rat) LD50: >2000 mg/kg ^[1]
	C.I. Solvent Yellow 82
Acute Toxicity	Oral (rat) LD50: >10000 mg/kg * ^[2]
	C.I. Solvent Yellow 62
	Oral (rat) LD50: >5000 mg/kg ^[2]
	C.I. Solvent Blue 45
	Oral (rat) LD50: >10000 mg/kg ^[2]
	C.I. Basic Red 12
	Oral (rat) LD50: 25 mg/kg ^[1]
Skin Irritation/Corrosion	No skin irritation
Serious Eye Damage/Irritation	No serious eye irritation
Respiratory or Skin sensitisation	May cause an allergic skin reaction.
Mutagenicity	No data available
Carcinogenicity	No data available
Reproductivity	No data available
STOT - Single Exposure	No data available
STOT - Repeated Exposure	May cause drowsiness or dizziness.
Aspiration Hazard	No data available

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Alcohol Based Ink

No data available for the mixture.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
Proprylene glycol monomethyl ether	LOW (Half-life = 56 days)	LOW (Half-life = 1.7 days)
rosin-colophony	HIGH	HIGH
C.I. Basic Red 12	HIGH	HIGH
C.I. Basic Yellow 37	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)
Proprylene glycol monomethyl ether	LOW (BCF = 2)
rosin-colophony	HIGH (LogKOW = 6.4607)
C.I. Basic Red 12	HIGH (LogKOW = 4.6657)
C.I. Basic Yellow 37	HIGH (LogKOW = 4.9479)

Mobility in soil

Ingredient	Mobility
ethanol	HIGH (KOC = 1)
Proprylene glycol monomethyl ether	HIGH (KOC = 1)
rosin-colophony	LOW (KOC = 21990)
C.I. Basic Red 12	LOW (KOC = 2410000)
C.I. Basic Yellow 37	LOW (KOC = 345000)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ► Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

▶ DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 TRANSPORT INFORMATION

Marine Pollutant	NO	
Land transport (DOT)		
UN number	1993	
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)	
Transport hazard class(es)	Class 3 Subrisk Not Applicable	
Packing group		
Environmental hazard	Not Applicable	
Special precautions for user	Hazard Label 3 Special provisions IB2, T7, TP1, TP8, TP28	

Air transport (ICAO-IATA / DGR)

UN number	1993		
UN proper shipping name	Flammable liquid, n.o.s. * (contains ethanol)		
	ICAO/IATA Class	3	
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable	
	ERG Code	зн	
Packing group			
Environmental hazard	Not Applicable		
	Special provisions		A3
	Cargo Only Packing Ir	nstructions	364
	Cargo Only Maximum	Qty / Pack	60 L
Special precautions for user	Passenger and Cargo	Packing Instructions	353
	Passenger and Cargo	Maximum Qty / Pack	5L
	Passenger and Cargo	Limited Quantity Packing Instructions	Y341
	Passenger and Cargo	Limited Maximum Qty / Pack	1L

Sea transport (IMDG-Code / GGVSee)

UN number	1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk Not Applicable
Packing group	
Environmental hazard	Not Applicable
Special precautions for user	EMS Number F-E , S-E Special provisions 274 Limited Quantities 1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ETHANOL(64-17-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS US - Alaska Limits for Air Contaminants US - Rhode Island Hazardous Substance List US - California Permissible Exposure Limits for Chemical Contaminants US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US - Hawaii Air Contaminant Limits US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants US - Idaho - Limits for Air Contaminants US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits US - Washington Permissible exposure limits of air contaminants US - Massachusetts - Right To Know Listed Chemicals US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US - Michigan Exposure Limits for Air Contaminants US ACGIH Threshold Limit Values (TLV) US - Minnesota Permissible Exposure Limits (PELs) US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): US ACGIH Threshold Limit Values (TLV) - Carcinogens US Department of Transportation (DOT), Hazardous Material Table US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Mutagens US DOE Temporary Emergency Exposure Limits (TEELs) US - Oregon Permissible Exposure Limits (Z-1) US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk Liquid Cargoes US - Pennsylvania - Hazardous Substance List US NIOSH Recommended Exposure Limits (RELs) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

PROPRYLENE GLYCOL MONOMETHYL ETHER(107-98-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	
US - California Permissible Exposure Limits for Chemical Contaminants	US - Washington Permissible exposure limits of air contaminants	
US - Hawaii Air Contaminant Limits	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values	
US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits	US ACGIH Threshold Limit Values (TLV)	
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV) - Carcinogens	
US - Michigan Exposure Limits for Air Contaminants	US Chemical Footprint Project - Chemicals of High Concern List	
US - Minnesota Permissible Exposure Limits (PELs)	US Clean Air Act - Hazardous Air Pollutants	
US - Oregon Permissible Exposure Limits (Z-1)	US Department of Transportation (DOT), Hazardous Material Table	
US - Pennsylvania - Hazardous Substance List	US DOE Temporary Emergency Exposure Limits (TEELs)	
US - Rhode Island Hazardous Substance List	US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk	
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	Liquid Cargoes	
US TSCA Chemical Substance Inventory - Interim List of Active Substances	US EPCRA Section 313 Chemical List	
•	US NIOSH Recommended Exposure Limits (RELs)	

ROSIN-COLOPHONY(8050-09-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List	US ACGIH Threshold Limit Values (TLV)
US - Washington Permissible exposure limits of air contaminants	US DOE Temporary Emergency Exposure Limits (TEELs)
US TSCA Chemical Substance Inventory - Interim List of Active Substances	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. SOLVENT YELLOW 82(12227-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

C.I. SOLVENT RED 218(82347-07-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

C.I. SOLVENT YELLOW 62(61901-95-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits

US - Washington Permissible exposure limits of air contaminants

C.I. SOLVENT BLUE 45(37229-23-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. BASIC RED 12(6320-14-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. SOLVENT YELLOW 79(12237-31-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

C.I. SOLVENT BLACK 45(94765-62-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

C.I. SOLVENT RED 91(61901-92-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

C.I. SOLVENT BLUE 5(1325-86-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. ACID VIOLET 66(12220-53-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

\parallel C.I. SOLVENT BLUE 70(12237-24-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

C.I. BASIC YELLOW 37(6358-36-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. ACID ORANGE 92(52256-37-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. SOLVENT BLACK 29(61901-87-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

SECTION 16 OTHER INFORMATION

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC – STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index