

# **SAFETY DATA SHEET**

12/26/2019

## **SECTION I - IDENTIFICATION**

#### **Material Name**

WAVERLY INSPIRATIONS LIQUID GILDING

#### **Company Information**

Plaid Enterprises, Inc. 3225 Westech Drive Norcross, GA 30092 Phone: 1-678-291-8259 Fax: 1-678-291-8363

Email: htrundle@PlaidOnline.Com

For transportation emergencies only call: 770-630-0380

For health emergencies call the Poison Control Center: 1-800-222-1222

## **SECTION II - HAZARDS IDENTIFICATION**

#### Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Skin Irritation - Category 2 Flammable Liquid 3 Aspiration Hazard - Category 1

#### **GHS Label Elements**

#### Symbol(s)







#### Signal Word(s)

Danger

#### **Hazard Statement(s)**

Causes skin irritation Flammable liquid and vapour May be fatal if swallowed and enters airways.

## **Precautionary Statement(s)**

#### Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep cool. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up.

#### Response

Specific treatment (see label). Do NOT induce vomiting. Rinse skin with water [or shower]. Take off immediately all contaminated clothing. IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

### SECTION III - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

		PEL/TLV	Max		
<b>Hazardous Ingredients</b>	CAS/EC#	(MG/M#)	% Weight	NTP	IARC
XYLENE	1330-20-7	434.00	45.50000	N	N
PETROLEUM DISTILLATE, HYDROTREATED LIGHT	64742-47-8	N/A	33.00000	N	N

## **SECTION IV - FIRST AID MEASURES**

FIRST AID MEASURES: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If swallowed, get prompt medical attention.

## SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): 290 C. AUTOIGNITION TEMPERATURE: N/A EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED Wear self-contained breathing apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS: FLAMMABLE, FLAMMABLE

### SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

## **SECTION VII - HANDLING AND STORAGE**

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

## SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use NIOSH-certified mask for dusts or mists. Use only with adequate ventilation.

OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED

WORK/HYGIENE PRACTICES: Wash hands immediately after use. When using do not eat, drink or smoke. Keep away from eyes. ENGINEERING CONTROLS: Do not store or use near heat or flame.

FOR HOME USE: CHILD-PROOF PACKAGING REQUIRED IN CONFORMANCE WITH 16CFR1700.15 a), b), and c) and meet the child test protocol requirements of one of CSA-Z76.1, ISO 8317 or 16 CFR 1700.20 or a standard that is at least equivalent.

KEEP OUT OF REACH OF CHILDREN.

#### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY: N/A

BOILING POINT: N/A MELTING POINT: N/A

VAPOR PRESSURE: N/A

SPECIFIC VAPOR DENSITY (AIR=1): N/A

SOLUBILITY IN WATER: N/A REACTIVITY IN WATER: NON-REACTIVE

## SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A STABILITY: STABLE CONDITIONS TO AVOID: N/A INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and smoke

#### SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: EYE IRRITANT. EXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. MAY BE HARMFUL BY BREATHING DUSTS OR MISTS. EXPOSURE MAY RESULT IN SHORTNESS OF BREATH, CHEST PAIN, CHEST TIGHTNESS, WHEEZING AND A COUGH.

The summated LD50 is 16395 mg/kg.

The summated LC50 is 6911.4 mg/cubic meter.

This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

## SECTION XII - ECOLOGICAL INFORMATION

NO HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

### SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE. WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

#### SECTION XIV - TRANSPORTATION INFORMATION

LAND TRANSPORT (US DOT) Xylenes DOT Proper Shipping Name 3 DOT Hazard Class: FLAMMABLE LIQUID DOT Hazard

Label: UN1307 UN/NA Number: III

## SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS: SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355): NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372): XYLENE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:
NONE

SUPPLEMENTAL STATE COMPLIANCE INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED UNDER NEW JERSEY'S RIGHT TO KNOW PROGRAM: XYLENE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRING NOTIFICATION TO THE STATE OF WASHINGTON UNDER THEIR CHILDREN'S SAFE PRODUCTS ACT: NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN FLORIDA'S TOXIC SUBSTANCE LIST: Xylene

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MAINE'S PRIORITY CHEMICAL LIST: NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS CONSIDERED BY VERMONT AS BEING OF VERY HIGH CONCERN TO CHILDREN:
NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MASSACHUSETTS HAZARDOUS SUBSTANCE LIST: Xylene

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MICHIGAN'S CRITICAL MATERIALS REGISTER: Dimethylbenzene

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MINNESOTA'S HAZARDOUS SUBSTANCES LIST: Dimethylbenzene

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN PENNSYLVANIA'S HAZARDOUS SUBSTANCES LIST: Benzene, Dimethylbenzene

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling:

DANGER:FLAMMABLE. Harmful or fatal if swallowed. VAPOR HARMFUL. EYE IRRITANT. Contains: XYLENE

PRECAUTIONS:Wash hands immediately after use. When using do not eat, drink or smoke. Keep away from eyes. Do not store or use near heat or flame. Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**FIRST AID TREATMENT:If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If swallowed, get prompt medical attention.

## **SECTION XVI - OTHER INFORMATION**

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 12/26/2019

Prepared by Duke OEM Toxicology

# **COLOR INFORMATION**

THIS SDS APPLIES TO THE FOLLOWING COLORS WHICH ARE ASSOCIATED WITH HAZARDOUS AND/OR NON-HAZARDOUS INGREDIENTS

<b>Product Color</b>	SKU	Hazardous Ingredient	
60981E SILVER		XYLENE	
	BRAND NAMES		
THIS SDS APPLIES TO THE FOLLOWING BRAND NA	MES		
Brand Nar	me		
WAVERLY IN	SPIRATIONS		